

NISSAN CABSTAR SPECIFICATIONS

Engine		
Code		ZD30DDTi
Type		Intercooler Turbo Diesel, 4 Cylinder, DOHC, Liquid-Cooled
Displacement	cc	2,953
Bore x Stroke		96.0 x 102.0
Max Power	KW (PS)/rpm	81 (110) / 2,800
Max Torque	Nm (kg-m)/rpm	276 (28.1) / 2,800
Compression Ratio		15.5 : 1
Fuel System		Common Rail, Electronic Fuel Injection Control
Fuel Economy (Combined)	KM/L	10.7
CO ₂ Emission	g/km	284
Transmission		
Type		5MT
Gear Ratio	1st	4.563
	2nd	2.528
	3rd	1.390
	4th	1.000
	5th	0.789
	Reverse	4.563
Final Gear Ratio		3.700
Steering/Suspension/Brakes		
Steering		Rack & Pinion with Power Assist
Suspension	Front	Independent Double-Wishbone Torsion Bar with Telescopic Shock Absorbers
	Rear	Rigid Axle Semi-Elliptic Leaf Springs with Telescopic Shock Absorbers
Brakes	System	Anti-lock Braking System (ABS), Electronic Brake-force Distribution (EBD)
	Front	Ventilated Disc
	Rear	Drum
Tyres & Wheels		
Tyres & Wheels	Front Tyres	175/80R15
	Rear Tyres	Double 155R13
Dimensions & Weight		
Overall Length	mm	4,690
Overall Width	mm	1,695
Overall Height	mm	1,990
Wheelbase	mm	2,500
Tread	Front/Rear (mm)	1,475 / 1,260
Min. Ground Clearance	mm	130
Overall Bed Length	mm	3,100
Overall Bed Width	mm	1,620
Overall Bed Height	mm	380
Ground-to-Floor Height	mm	740
Gross Vehicle Weight	kg	3,500
Curb Weight	kg	1,760 - 1,780
Min. Turning Radius (Curb to Curb)	m	4.4
Capacity		
Seating Capacity	No. of Persons	1 Driver + 2 Passengers
Fuel Tank Capacity	L	65
Electrical System		
Battery	VAH	12 volt, 70 Amp
Alternator	VAH	12 volt, 135 Amp

Nissan Motor Co., Ltd. reserves the right to make any changes without notice concerning colours, equipment or specifications detailed in this brochure, or to discontinue individual models. The colors of vehicles delivered may differ slightly from those in this brochure.

The specifications vary for different countries depending on local market conditions.

Please consult your local dealer to ensure that the vehicle delivered accords with your expectations.