

## GT-R BLACK EDITION SPECIFICATIONS

Engine			
Code		VR38	
Type		DOHC, 24 Valves, 6-Cylinder, Twin Turbo	
Displacement	cc	3,799	
Bore x Stroke	mm	95.5 x 88.4	
Max Power	PS(kW)/rpm	570 (419) / 6,800	
Max Torque	Nm(kg-m)/rpm	632 (64.4) / 3,300 - 5,800	
Compression Ratio		9.0	
Transmission			
Type		GR6 Dual Clutch Transmission	
Gear Ratio	1st	4.056	
	2nd	2.301	
	3rd	1.595	
	4th	1.248	
	5th	1.001	
	6th	0.796	
	Reverse	3.383	
Final Gear Ratio		3.700	
Limited Slip Differential		1.5 Way Mechanical	
Fuel/CO <sub>2</sub> Emission			
Fuel System		Electronic Fuel Injection	
Fuel Consumption (Combined Cycle)	L/100km	11.7	
CO <sub>2</sub> Emission (Combined Cycle)	g/km	279	
Steering/Suspension/Brakes			
Steering		Power Assisted Hydraulic, Rack & Pinion	
Suspension	Front	Bilstein DampTronic Shock Absorbers, Independent Double-Wishbone	
	Rear	Bilstein DampTronic Shock Absorbers, Multi-Link	
Brakes	Caliper	Front	Aluminium 6-Pod Mono-Block
		Rear	Aluminium 4-Pod Mono-Block
	Rotor	Front	390mm Drilled Floating Rotors
		Rear	380mm Drilled Floating Rotors
Wheels/Tyres			
Wheels		20-Inch Aluminium Forged	
Tyres	Type	Dunlop SP Sport MAXX GT 600 DSST CTT	
	Front	255/40R20	
	Rear	285/35R20	
Dimensions/Weight			
Overall Length	mm	4,710	
Overall Width	mm	1,895	
Overall Height	mm	1,370	
Wheelbase	mm	2,780	
Thread	Front	mm	1,590
	Rear	mm	1,600
Min. Ground Clearance	mm	110	
Min. Turning Radius (Curb to Curb)	Curb to Curb	m	5.7
Curb Weight	kg	1,752	
Capacities			
Seating	Persons	2 + 2	
Fuel Tank	L	74	

Tan Chong Motor Sales Pte Ltd reserves the right to make any changes without notice concerning colours, equipment and specifications detailed in this brochure, or to discontinue individual models. The colours of vehicles may differ slightly from those in this brochure.