

SPECIFICATIONS

NISSAN JUKE 1.6L

		2WD
Engine		
Code		HR16DE
Type		4-cyl. in-line, DOHC
Displacement	cc	1598
Bore x stroke	mm	78.0 x 83.6
Max. power	kW (PS)/rpm	86 (116) / 6000
Max. torque	Nm /rpm	158 / 4000
Compression ratio		10.7
Fuel system		ECCS, electronic fuel injection control
Transmission		
Type		Xtronic CVT
Gear Ratios		4.006 - 0.550
Final gear ratio (hypoid final gear)		6.386
Steering/Suspension/Brakes		
Steering		Vehicle speed-sensitive power-assisted rack-and-pinion steering
Min. turning radius (curb to curb)m		5.3
Suspension	front	Independent strut
	rear	Torsion beam
Brakes	system	4-wheel Anti-lock Braking System (ABS), Electronic Brake force Distribution (EBD) and Brake Assist (BA)
	front	Ventilated discs
	rear	discs
Wheels/Tires		
Wheels		17 x 7J alloy
Tires		215/55R17
Dimensions/Weights		
Overall length	mm	4135
Overall width	mm	1765
Overall height	mm	1565
Wheelbase	mm	2530
Tread	front/rear mm	1525/1523
Min. ground clearance	mm	165
Curb weight	kg	1218
Gross vehicle weight	kg	1670
Capacities		
Seating	persons	5
Fuel tank	L	46
Trunk	L (VDA)	354
Fuel/CO2 Emission		
Fuel consumption (Urban Cycle)	L/100km	8.3
Fuel consumption (Combined Cycle)		6.3
CO2 (Combined Cycle)	g/km	145

Tan Chong Motor Sales Pte Ltd reserves the right to make any changes without notice concerning colours, equipment and specifications detailed in this brochure, or to discontinue individual models. The colours may differ slightly from those in this brochure.